

# TECATEC SAN Flax Fibres Semipreg

---

## 1. Identification of the article and of the company

**Trade name:**

TECATEC SAN NAFX XYYY CP VXX natural

**Application:**

Semi-finished engineering plastics

**Note:**

The present product is an article in the sense of regulation (EC) No 1907/2006 (REACH).

**Supplier:**

Ensinger GmbH  
Wilfried-Ensinger-Straße 1  
D - 93413 Cham  
Tel. +49 9971 396 0  
www.ensingerplastics.com

**Competent person:**

phib@ensingerplastics.com

---

## 2. Hazards identification

**Classification and labelling:**

The product is not classified and doesn't need any labelling.

**Other hazards:**

Vigorous abrasion of flax fibre products yield microscopic fibre particles. Prolonged inhalation of alveolar fibre dust may cause lung damage.

---

## 3. Composition/information on ingredients

**Description:**

Article based on styrene-acrylonitrile copolymer, CAS No 9003-54-7, and styrene-acrylonitrile-maleic anhydride copolymer, CAS No 27812-34-6.

Containing flax fibre fabric.

Possibly containing additives and processing aids.

**Information on ingredients:**

The product doesn't contain any substance, which is supposed to be released under normal or reasonably foreseeable conditions of use.

## TECATEC SAN Flax Fibres Semipreg

---

### 4. First aid measures

**After inhalation:**

After inhalation of product dust or thermal decomposition products, remove person from the danger zone. Fresh air, oxygen supply, apply artificial respiration if necessary. Keep quiet and warm and seek medical help.

**After skin contact:**

After contact with product dust wash skin with plenty of water and soap. In the event of skin reactions seek medical advice.

**After eye contact:**

If a foreign body (splinter, chip) enters the eye do not rub. Immobilize the eye, cover both eyes with bandages, consult an eye specialist.

**Indication of any immediate medical attention and special treatment needed:**

Treat symptomatically.

---

### 5. Firefighting measures

**Suitable extinguishing media:**

Water spray, alcohol-resistant foam, carbon dioxide, dry chemical foam.

**Unsuitable extinguishing media:**

Water jet.

**Special hazards arising from the article:**

With carbonization and incomplete combustion toxic gases develop, predominantly carbon dioxide and carbon monoxide. The development of further fission and oxidation products is dependent on the conditions of burning.

Traces of other toxic substances may develop under certain conditions of burning.

The formation of thick smoke and the release of hydrogen cyanide and nitrogen oxides are possible.

**Advice for firefighters:**

If exposed to fumes and carbonization gases during fire-fighting measures, rescue operations and cleanup wear a self-contained breathing apparatus.

The product ignites in a flame and continues to burn on removal of the source.

In an advanced state of fire, the molten polymer must be cooled with water. Water used to extinguish the fire and fire remainders must be collected and water disposed of, in accordance with local regulations.

## **TECATEC SAN Flax Fibres Semipreg**

---

### **6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:**

Avoid dust formation. Take precautionary measures against static discharges. Keep away from sources of ignition.

No smoking.

Avoid contact with skin and eyes. Use personal protective clothing.

**Environmental precautions:**

Let not enter surface water and sewage water system.

**Methods and material for containment and cleaning up:**

Mechanical cleaning up.

Avoid dry sweeping. Use an appropriate suction device for cleaning to avoid the generation of dust.

---

### **7. Handling and storage**

**Precautions for safe handling:**

Avoid overheating of material by improper handling.

Mechanical processing should generate as little dust as possible. A local extraction system must be installed, or else a proper ventilation of the workplace must be guaranteed.

Take measures against static discharge. Keep away from sources of ignition.

Avoid inhalation of dust/mist/vapour.

General industrial hygiene regulations are to be observed.

Wash hands before breaks and at the end of workday.

Tobacco should not be kept in the workplace.

Do not eat, drink or smoke in the workplace.

**Conditions for safe storage, including any incompatibilities:**

The appropriate company regulations for fire prevention are to be followed.

## TECATEC SAN Flax Fibres Semipreg

---

### 8. Exposure controls/personal protection

**Control parameters:**

The general limit for dust is valid.

**Exposure controls:**

The working area should be well ventilated.

Technical measures have priority over personal protective equipment.

**Respiratory protection:**

Wear protective breathing apparatus in case of dust exposure and/or insufficient ventilation. Wear dust mask filter type P3 or FFP3 (DIN EN 143/DIN EN 149).

**Eye/face protection:**

For mechanical operations wear safety glasses with side pieces or fully closed and tight-fitting goggles (DIN EN 166).

**Hand protection/skin protection:**

Skin protection should be used (barrier cream containing tanning agent).

For mechanical processing of fibre reinforced products loose fitting, tight work clothes should be worn. Persons with sensitive skin should wear leather protective gloves (DIN EN 388).

---

### 9. Physical and chemical properties

**Appearance:**

solid (semi-finished parts, wound on rolls)

**Melting point/Melting range:**

> 105 °C

**Relative density:**

ca. 1,24 g/cm<sup>3</sup>

**Flash point:**

N/A (solid)

**Explosive properties:**

N/A

**Solubility(ies):**

insoluble (water, 20 °C)

**Odour/odour threshold:**

product-specific

**Initial boiling point and Boiling range:**

N/A (solid)

**Decomposition temperature:**

> 300 °C

**Flammability (solid, gas):**

> 400 °C

**Vapour pressure:**

N/A (solid)

**Partition coefficient: n-octanol/water:**

N/A

## **TECATEC SAN Flax Fibres Semipreg**

---

### **10. Stability and reactivity**

**Chemical stability:**

Product is stable. No hazardous reactions known when stored and handled according to instructions and used for its intended purpose.

**Conditions to avoid:**

Do not heat to a temperature above the melting or decomposition temperature.

**Incompatible materials:**

Strong oxidizing agents.

**Hazardous decomposition products:**

By strong overheating of the material hydrogen cyanide, monomers, oligomers, hydrocarbons and other gaseous decomposition products can be generated.

---

### **11. Toxicological information**

**Acute toxicity:**

Increased inhalation of fine fibre dust can cause coughing, shortness of breath.

**Chronic toxicity:**

Natural fibres, e.g. from flax, cannot be broken down by the human body. Alveolar dusts trigger an immune reaction in the lungs. This results in increased mucus production, coughing, shortness of breath. Increased/prolonged inhalation of alveolar dusts can cause a chronic disease of the lungs (byssinosis), similar to chronic bronchitis.

**Other information:**

According to the information available to us, the product does not cause any adverse health effects when handled and used properly and in compliance with the safety measures regarding dust avoidance.

---

### **12. Ecological information**

No relevant information available.

Due to the consistency of the product a disperse distribution in the environment is not likely. Therefore, according to the present state of knowledge negative ecological effects are not expected.

## TECATEC SAN Flax Fibres Semipreg

---

### 13. Disposal considerations

**Waste treatment methods:**

Product residues can be recycled or treated in an energy recovery plant.  
When segregated, unpolluted product residues can be recycled mechanically.

**European waste catalogue:**

The unpolluted product has no dangerous properties and is therefore not a hazardous waste within the meaning of regulation on the European List of wastes.

**Waste codes/waste identification:**

The exact assignment to a waste code must be carried out source- and use-related.  
Proposals for the waste code numbers based on the probable use of the unpolluted product:  
07 02 13 (waste plastic)  
20 01 39 (plastics from separately collected fractions)

**Packaging:**

Uncontaminated or cleaned packaging can be recycled without verification.

---

### 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

---

### 15. Regulatory information

**Safety, health and environmental regulations/legislation specific:**

According to annex II of the REACH regulation there is no legal obligation to compile safety data sheets for articles. We explicitly would like to point out that the present product handling information sheet (PHIS) is a voluntary information sheet for the handling of products, based on the same principle as our safety data sheets.  
Information pursuant to Article 33 of Regulation (EC) No 1907/2006 (REACH): That article doesn't contain any substance meeting the criteria in Article 57 and identified in accordance with Article 59(1) in a concentration above 0,1 % weight by weight (w/w).

**EU regulations:**

According to regulation (EC) No 1272/2008 (CLP) articles are not subject to classification and labelling requirements.

**Chemical safety assessment:**

A chemical safety assessment is not necessary for articles and therefore has not been carried out.

**National regulations:**

Storage class VCI/TRGS 510 (Germany): 11 (flammable solid materials)

## **TECATEC SAN Flax Fibres Semipreg**

---

### **16. Other information**

**Indication of changes:**

First issue, status as of 05/22.

---

Our information and statements reflect the current state of our knowledge and shall inform about our products and their applications. They do not assure or guarantee chemical resistance, quality of products and their merchantability in a legally binding way. Our products are not defined for use in medical or dental implants. Existing commercial patents have to be observed. The corresponding values and information are no minimum or maximum values, but guideline values. They do not represent guaranteed properly values and therefore they must not be used for specification purposes. The customer is solely responsible for the quality and suitability of products for the application and has to test usage and processing prior to use. It is the user`s responsibility to ensure that existing legislation and regulation are followed.